

## PCT

## INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference <b>P62831</b>	<b>FOR FURTHER ACTION</b> see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.	
International application No. <b>PCT/GB 99/ 00595</b>	International filing date (day/month/year) <b>26/02/1999</b>	(Earliest) Priority Date (day/month/year) <b>26/02/1998</b>
Applicant <b>FENLAND LAUNDRIES LIMITED et al.</b>		

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 3 sheets.



It is also accompanied by a copy of each prior art document cited in this report.

## 1. Basis of the report

- a. With regard to the **language**, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.



the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).

- b. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international search was carried out on the basis of the sequence listing :



contained in the international application in written form.



filed together with the international application in computer readable form.



furnished subsequently to this Authority in written form.



furnished subsequently to this Authority in computer readable form.



the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.



the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2. ☐ **Certain claims were found unsearchable** (See Box I).

3. ☐ **Unity of invention is lacking** (see Box II).

4. With regard to the **title**,



the text is approved as submitted by the applicant.



the text has been established by this Authority to read as follows:

5. With regard to the **abstract**,



the text is approved as submitted by the applicant.



the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. The figure of the **drawings** to be published with the abstract is Figure No.



as suggested by the applicant.



because the applicant failed to suggest a figure.



because this figure better characterizes the invention.

3, 5



None of the figures.

## INTERNATIONAL SEARCH REPORT

International Application No

/GB 99/00595

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A41D13/00 A41D31/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A41D B01D H05F H01B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4 546 497 A (ONO KAZUMASA ET AL) 15 October 1985 (1985-10-15) cited in the application column 2, line 35-40; figure 2 ---	1-6
Y	US 4 606 968 A (THORNTON PETER B ET AL) 19 August 1986 (1986-08-19) column 2, line 34 column 4, line 9-17 column 4, line 30,31; figure 2 ---	1-6
A	US 5 715 536 A (BANKS DAVID L) 10 February 1998 (1998-02-10) cited in the application column 2, line 65 column 3, line 24-30; figures 3,4 --- -/--	1,2,6



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&amp;" document member of the same patent family

Date of the actual completion of the international search

28 July 1999

Date of mailing of the international search report

04/08/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Monné, E

## INTERNATIONAL SEARCH REPORT

International Application No

/GB 99/00595

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 274 454 A (GALLAGHER ELECTRONICS LTD ; JOUBERT SA (FR)) 13 July 1988 (1988-07-13) column 2, line 21-45; figures ----	1, 3
A	DE 296 20 811 U (NSP SICHERHEITS PRODUKTE GMBH) 16 January 1997 (1997-01-16) claims 1-4; figures 5, 6 ----	1, 2, 6
A	GB 1 221 724 A (LOOMS) 10 February 1971 (1971-02-10) page 1, line 22-37 page 1, line 76 page 2, line 20-29; figures 2, 3 -----	1, 6

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

/GB 99/00595

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4546497	A	15-10-1985	DE 3340224 T WO 8303526 A	05-04-1984 27-10-1983
US 4606968	A	19-08-1986	EP 0149624 A JP 60028546 A WO 8500556 A US 4557968 A	31-07-1985 13-02-1985 14-02-1985 10-12-1985
US 5715536	A	10-02-1998	CA 2219848 A DE 19754901 A GB 2320669 A JP 10317212 A	26-06-1998 02-07-1998 01-07-1998 02-12-1998
EP 0274454	A	13-07-1988	AT 86779 T AU 614504 B AU 1010388 A CA 1320533 A DE 3878934 A DE 3878934 T DK 3988 A FI 880033 A IE 63002 B JP 63198209 A PH 24578 A PT 86496 A, B US 4861645 A	15-03-1993 05-09-1991 07-07-1988 20-07-1993 15-04-1993 21-10-1993 07-07-1988 07-07-1988 08-03-1995 16-08-1988 17-08-1990 30-01-1989 29-08-1989
DE 29620811	U	16-01-1997	NONE	
GB 1221724	A	10-02-1971	NONE	

REC'D 16 JUN 2000

WIPO

PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference P62831		See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416) <b>FOR FURTHER ACTION</b>	
International application No. PCT/GB99/00595	International filing date (day/month/year) 26/02/1999	Priority date (day/month/year) 26/02/1998	
International Patent Classification (IPC) or national classification and IPC A41D13/00			
Applicant FENLAND LAUNDRIES LIMITED et al.			

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.



2. This REPORT consists of a total of 5 sheets, including this cover sheet.

☒ This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

These annexes consist of a total of 15 sheets.

3. This report contains indications relating to the following items:

- I ☒ Basis of the report
- II ☐ Priority
- III ☐ Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
- IV ☐ Lack of unity of invention
- V ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- VI ☐ Certain documents cited
- VII ☒ Certain defects in the international application
- VIII ☒ Certain observations on the international application

Date of submission of the demand  27/09/1999	Date of completion of this report  13. 06. 00
Name and mailing address of the international preliminary examining authority:   European Patent Office D-80298 Munich Tel. +49 89 2399 - 0 Tx: 523656 epmu d Fax: +49 89 2399 - 4465	Authorized officer  Pollet, D  Telephone No. +49 89 2399 7516 

**INTERNATIONAL PRELIMINARY  
EXAMINATION REPORT**

International application No. PCT/GB99/00595

**I. Basis of the report**

1. This report has been drawn on the basis of *(substitute sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments.)*:

**Description, pages:**

1-13 as received on 01/04/2000 with letter of 29/03/2000

**Claims, No.:**

1-15 as received on 01/04/2000 with letter of 29/03/2000

**Drawings, sheets:**

1/7-7/7 as originally filed

2. The amendments have resulted in the cancellation of:

- ☐ the description, pages:  
☐ the claims, Nos.:  
☐ the drawings, sheets:

3. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)):

4. Additional observations, if necessary:

**INTERNATIONAL PRELIMINARY  
EXAMINATION REPORT**

International application No. PCT/GB99/00595

**V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**

**1. Statement**

Novelty (N)	Yes: Claims 1-15
	No: Claims
Inventive step (IS)	Yes: Claims 1-15
	No: Claims
Industrial applicability (IA)	Yes: Claims 1-15
	No: Claims

**2. Citations and explanations**

**see separate sheet**

**VII. Certain defects in the international application**

The following defects in the form or contents of the international application have been noted:

**see separate sheet**

**VIII. Certain observations on the international application**

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

**see separate sheet**

**Re Item V**

**Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**

Reference is made to the following documents:

D1: US-A-4 546 497 (cited in the application as filed originally)

D2: US-A-4 606 968

- V.1 The document (D1) is regarded as being the closest prior art to the subject-matter of claim 1, and shows an overlapped or butt-joined seam for antistatic clothing comprising an electrically conductive tape (9) bridging the junction between adjacent pieces of cloth (5, 6), which incorporate electrically conductive fibres (7, 8).

It is known that the electrically conductive fibres in each piece of cloth are unlikely to make satisfactory contact with one another when stitched together in an article of workwear resulting in an unsatisfactory electrical connection across the seams.

The problem the present invention seeks to solve is to earth satisfactorily an antistatic workwear.

This problem is solved by sandwiching in the seams of the antistatic workwear an electrically conductive strip or tape (20), which incorporates a plurality of electrically conductive yarns (22, 131) having a larger diameter than the conductive yarns (21) included in the various components of the workwear. The significance of this feature is that the larger diameter yarns (22, 131) project from the strip or tape by an amount greater than the conductive yarns (21) in the components and consequently increase the electrical conductivity of the seam.

No hint or indication to the above mentioned feature was found in the teachings of the prior art documents. Document (D2) describes an electrostatic dissipating fabric (10), depicted in figures 1-2, constructed of a woven or knitted base fabric (12, 14 e.g., non-conductive man-made fibres) having an integrally woven or knitted grid structure formed from a static discharge yarn (16, 18), which is raised

above the surface of the base fabric as seen in Fig. 2 (i.e., R-S) thereby resulting in an increased electrostatic dissipation performance (col. 5, l. 64-67). However, document (D2) does not suggest to include strips of this material in between the seam of conductive fabrics having conductive yarns of a smaller diameter than the conductive yarns in the strip.

Consequently, having regard to the available prior art, the subject-matter of claim 1 appears to be new and inventive within the meaning of Articles 33(2) and (3) PCT.

- V.2 The dependent claims 2-15 relate to further details of the antistatic workwear according to claim 1 and likewise appear to meet the requirements of articles 33(2) and (3) PCT.

**Re Item VII**

**Certain defects in the international application**

According to the requirements of Rule 10.2 PCT, the terminology shall be consistent throughout the application. This requirement is not met in view of the use of the expressions 'yarns (21 or 22)' in claim 7 and 'terminal (25)' in claim 11 and fastening means (25,...) in claim 13.

**Re Item VIII**

**Certain observations on the international application**

The application does not meet the requirements of Article 6 PCT, because the terminology 'conductive yarns' used in claims 1 to 5 is confusing in that there is no clear distinction between the conductive yarns (21) incorporated in the components and the conductive yarns (22, 131) incorporated in the strip or tape.

From the  
INTERNATIONAL PRELIMINARY EXAMINING AUTHORITY

**PCT**

**NOTIFICATION OF TRANSMITTAL OF  
THE INTERNATIONAL PRELIMINARY  
EXAMINATION REPORT**  
(PCT Rule 71.1)

To:

LOVEN, Keith, James  
Loven & Co.  
Quantum House  
30 Tentercroft Street  
Lincoln LN5 7DB  
GRANDE BRETAGNE

Date of mailing  
(day/month/year)

**13. 06. 00**

Applicant's or agent's file reference  
**P62831**

**IMPORTANT NOTIFICATION**

International application No.  
**PCT/GB99/00595**

International filing date (day/month/year)  
**26/02/1999**

Priority date (day/month/year)  
**26/02/1998**

Applicant

**FENLAND LAUNDRIES LIMITED et al.**

1. The applicant is hereby notified that this International Preliminary Examining Authority transmits herewith the international preliminary examination report and its annexes, if any, established on the international application.
2. A copy of the report and its annexes, if any, is being transmitted to the International Bureau for communication to all the elected Offices.
3. Where required by any of the elected Offices, the International Bureau will prepare an English translation of the report (but not of any annexes) and will transmit such translation to those Offices.

**4. REMINDER**

The applicant must enter the national phase before each elected Office by performing certain acts (filing translations and paying national fees) within 30 months from the priority date (or later in some Offices) (Article 39(1)) (see also the reminder sent by the International Bureau with Form PCT/IB/301).

Where a translation of the international application must be furnished to an elected Office, that translation must contain a translation of any annexes to the international preliminary examination report. It is the applicant's responsibility to prepare and furnish such translation directly to each elected Office concerned.

For further details on the applicable time limits and requirements of the elected Offices, see Volume II of the PCT Applicant's Guide.

Name and mailing address of the IPEA/



European Patent Office  
D-80298 Munich  
Tel. +49 89 2399 - 0 Tx: 523656 epmu d  
Fax: +49 89 2399 - 4465

Authorized officer

**Dumas, E**

Tel. +49 89 2399-7531



# PATENT COOPERATION TREATY

## PCT

### INTERNATIONAL PRELIMINARY EXAMINATION REPORT



(PCT Article 36 and Rule 70)

Applicant's or agent's file reference <b>P62831</b>	<b>FOR FURTHER ACTION</b> See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)	
International application No. <b>PCT/GB99/00595</b>	International filing date (day/month/year) <b>26/02/1999</b>	Priority date (day/month/year) <b>26/02/1998</b>
International Patent Classification (IPC) or national classification and IPC <b>A41D13/00</b>		
Applicant <b>FENLAND LAUNDRIES LIMITED et al.</b>		

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.
2. This REPORT consists of a total of 5 sheets, including this cover sheet.  
  
☒ This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).  
  
 These annexes consist of a total of 15 sheets.

3. This report contains indications relating to the following items:

- I ☒ Basis of the report
- II ☐ Priority
- III ☐ Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
- IV ☐ Lack of unity of invention
- V ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- VI ☐ Certain documents cited
- VII ☒ Certain defects in the international application
- VIII ☒ Certain observations on the international application

Date of submission of the demand  <b>27/09/1999</b>	Date of completion of this report  <b>13. 06. 00</b>
Name and mailing address of the international preliminary examining authority:   <b>European Patent Office</b> <b>D-80298 Munich</b> <b>Tel. +49 89 2399 - 0 Tx: 523656 epmu d</b> <b>Fax: +49 89 2399 - 4465</b>	Authorized officer  <b>Pollet, D</b>  Telephone No. <b>+49 89 2399 7516</b>  

**INTERNATIONAL PRELIMINARY  
EXAMINATION REPORT**

International application No. PCT/GB99/00595

**I. Basis of the report**

1. This report has been drawn on the basis of (*substitute sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments.*):

**Description, pages:**

1-13 as received on 01/04/2000 with letter of 29/03/2000

**Claims, No.:**

1-15 as received on 01/04/2000 with letter of 29/03/2000

**Drawings, sheets:**

1/7-7/7 as originally filed

2. The amendments have resulted in the cancellation of:

- ☐ the description, pages:  
☐ the claims, Nos.:  
☐ the drawings, sheets:

3. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)):

4. Additional observations, if necessary:

**INTERNATIONAL PRELIMINARY  
EXAMINATION REPORT**

International application No. PCT/GB99/00595

**V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**

**1. Statement**

Novelty (N)	Yes: Claims 1-15
	No: Claims
Inventive step (IS)	Yes: Claims 1-15
	No: Claims
Industrial applicability (IA)	Yes: Claims 1-15
	No: Claims

**2. Citations and explanations**

**see separate sheet**

**VII. Certain defects in the international application**

The following defects in the form or contents of the international application have been noted:

**see separate sheet**

**VIII. Certain observations on the international application**

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

**see separate sheet**

**INTERNATIONAL PRELIMINARY  
EXAMINATION REPORT - SEPARATE SHEET**

---

International application No. PCT/GB99/00595

**Re Item V**

**Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**

Reference is made to the following documents:

D1: US-A-4 546 497 (cited in the application as filed originally)

D2: US-A-4 606 968

- V.1 The document (D1) is regarded as being the closest prior art to the subject-matter of claim 1, and shows an overlapped or butt-joined seam for antistatic clothing comprising an electrically conductive tape (9) bridging the junction between adjacent pieces of cloth (5, 6), which incorporate electrically conductive fibres (7, 8).

It is known that the electrically conductive fibres in each piece of cloth are unlikely to make satisfactory contact with one another when stitched together in an article of workwear resulting in an unsatisfactory electrical connection across the seams.

The problem the present invention seeks to solve is to earth satisfactorily an antistatic workwear.

This problem is solved by sandwiching in the seams of the antistatic workwear an electrically conductive strip or tape (20), which incorporates a plurality of electrically conductive yarns (22, 131) having a larger diameter than the conductive yarns (21) included in the various components of the workwear. The significance of this feature is that the larger diameter yarns (22, 131) project from the strip or tape by an amount greater than the conductive yarns (21) in the components and consequently increase the electrical conductivity of the seam.

No hint or indication to the above mentioned feature was found in the teachings of the prior art documents. Document (D2) describes an electrostatic dissipating fabric (10), depicted in figures 1-2, constructed of a woven or knitted base fabric (12, 14 e.g., non-conductive man-made fibres) having an integrally woven or knitted grid structure formed from a static discharge yarn (16, 18), which is raised

**INTERNATIONAL PRELIMINARY  
EXAMINATION REPORT - SEPARATE SHEET**

---

International application No. PCT/GB99/00595

above the surface of the base fabric as seen in Fig. 2 (i.e., R-S) thereby resulting in an increased electrostatic dissipation performance (col. 5, l. 64-67). However, document (D2) does not suggest to include strips of this material in between the seam of conductive fabrics having conductive yarns of a smaller diameter than the conductive yarns in the strip.

Consequently, having regard to the available prior art, the subject-matter of claim 1 appears to be new and inventive within the meaning of Articles 33(2) and (3) PCT.

- V.2 The dependent claims 2-15 relate to further details of the antistatic workwear according to claim 1 and likewise appear to meet the requirements of articles 33(2) and (3) PCT.

**Re Item VII**

**Certain defects in the international application**

According to the requirements of Rule 10.2 PCT, the terminology shall be consistent throughout the application. This requirement is not met in view of the use of the expressions 'yarns (21 or 22)' in claim 7 and 'terminal (25)' in claim 11 and fastening means (25,...) in claim 13.

**Re Item VIII**

**Certain observations on the international application**

The application does not meet the requirements of Article 6 PCT, because the terminology 'conductive yarns' used in claims 1 to 5 is confusing in that there is no clear distinction between the conductive yarns (21) incorporated in the components and the conductive yarns (22, 131) incorporated in the strip or tape.

1101.04.00

- 1 -

## DISSIPATION OF STATIC ELECTRICITY IN WORKWEAR

### Field of the Invention

This invention relates to the dissipation of static electricity in specialised workwear and more particularly to antistatic workwear, that is clothing or other garments worn for work.

### Background to the Invention

As electronic components become smaller and more sensitive they may be easily damaged by static electrical charges. It is therefore important that operatives engaged in the manufacture of such components are at earth potential, that is they do not carry a static electrical charge. For this purpose specialised workwear, for use in the micro electronics industry, has been developed made from tightly woven fabric incorporating a grid or stripe of electrically conductive yarn. This is designed to dissipate static electrical charges which would otherwise build-up as the article of workwear is worn. In particularly sensitive situations static dissipation is improved by earthing the operator, the workwear or both.

As well as in the microelectronics industry, the control of static build-up in workwear is also important in the pharmaceutical and microbiological industries, for three main reasons. Firstly, the build up of an electrostatic charge may cause attraction or repulsion of bacteria or microscopic particles of active pharmaceutical agents, thereby changing the performance of the protective workwear, which may not only serve to protect the product from contamination but also protect the wearer from contact with the materials being handled. The performance of the workwear is therefore closely specified, and the effects of electrostatic attraction or repulsion of materials may be that the performance standard is not achieved in practice. By reducing the electrostatic charge to zero or a very low voltage consistently, the performance of the workwear can be guaranteed. Secondly, the build-up of electrostatic charge can involve a risk of discharge to neighbouring earthed surfaces, giving rise to sparks which can ignite flammable vapours used in processing, for example. The third reason is allied to the second, in that the discharge of high electrostatic voltages through sensitive electronic measuring or monitoring equipment can lead to false readings or to damage. In the

M 0 1 . 0 4 . 0 0

- 2 -

context of medical work, false readings or disruption to monitoring equipment could have very serious consequences for patients, for example.

Difficulties can arise in relation to such workwear due to the fact that the conductive filaments are woven into the fabric and as such come to the surface of the fabric relatively infrequently and in an erratic manner. As a result if one piece of fabric is placed on top of another, as occurs, for example in the case of a seam between adjacent parts of an article of workwear, the electrically conductive filaments in each piece of fabric are unlikely to make contact or satisfactory contact with one another with the result that it is unlikely a satisfactory electrical connection will be made across the seam.

10 A similar problem arises in the case of an article of workwear consisting of more than one garment, for example where a hood or an item of footwear are used in association with a main garment. As a result it is difficult to earth all of the garments from a single earthing point.

In US-A-5 715 536 there is disclosed a static electricity dissipating garment in which a continuous conducting ribbon extends through all the seams and is connected to a grounding wire. Similarly, in US-A-4 546 497 there is disclosed antistatic clothing incorporating electroconductive tape in the seams. US-A-4606968 discloses a base fabric, for use in antistatic garments, having an integrally woven or knitted grid structure which is raised above the surface of the base fabric to provide increased electrostatic dissipation performance, the grid being formed from a static discharge yarn plied to a carrier yarn which is then woven or knitted into the fabric in the warp direction.

20

It is therefore known for antistatic workwear to comprise a plurality of components incorporating electrically conductive yarns and an electrically conductive member bridging the junction between adjacent components.

25 A problem which arises with antistatic workwear is that the antistatic properties tend to degrade with repeated cleaning. For example, workwear may be washed, chemically treated (so-called "dry cleaning") and/or radiation treated to ensure that it is clean and sterile. It has been found that the residual static voltage on the workwear tends to rise with repeated cleaning cycles until it reaches an unacceptable level. For conventional workwear of the types described, it has been found that this state is reached long before the workwear has otherwise come to the end of its working life.

30

11 01 04 00

- 3 -

### Summary of the Invention

According to the present invention an article of workwear has the electrical conductivity between adjacent components enhanced by forming the electrically conductive member from a strip or tape incorporating a plurality of electrically conductive  
5 yarns, which are of larger diameter than the conductive yarns in the components, have alternate portions exposed at opposite faces of the strip or tape, and are pressed into conducting engagement with at least some of the conductive yarns in both adjacent components. Throughout the specification and the claims the word "yarn" is used generically to any yarn, fibre, filament or equivalent component of a workwear fabric, strip  
10 or tape. At least some of the electrically conductive yarns may be formed from a carbon-coated polyamide or a conductive polyester.

The conductive yarns in the strip or tape are preferably sharply bent by the structure of the strip or tape to promote a corona discharge. The conductive yarns in the components are preferably more widely spaced than the conductive yarns in the  
15 strip or tape. The conductive yarns in the components preferably have a diameter of between 0.01-0.05mm, and the conductive yarns in the strip or tape a diameter of between 0.5-1.0mm.

The strip or tape is preferably stitched to each of the adjacent components. However, it will be understood that other methods of attachment may be used, for example welding using heat, ultrasonics or high frequency electromagnetic radiation, or  
20 adhesives.

Preferably, each component is of woven construction.

The term "component" is used herein to refer both to adjacent components of a single article of workwear and adjacent garments or other items which together form a  
25 complete article of workwear. A single article of workwear may, for example, be formed from a number of panels connected together by seams, each of the panels comprising a component of the complete article of workwear. Alternatively an item of workwear may consist of a number of separate articles which are worn together such as a body garment, a hood and articles of footwear, each of which comprises a component  
30 of the overall article of workwear.

M 0 1 . 0 4 . 0 0

- 4 -

Where the article of workwear comprises a single garment, the components may comprise adjacent panels from which the garment is constructed and which are connected to one another by seams. In such cases the strip or tape may extend transversely across each seam formed between adjacent components of the article so as to bridge the seam and interconnect electrically conductive members incorporated in the respective panels. Alternatively the strip or tape may be incorporated longitudinally into a seam formed between adjacent components whereby the strip or tape will be in surface contact with each of the panels connected together at the seam.

Where the components comprise a plurality of separate garments employed together to form a complete article of workwear, the strip or tape may incorporate fastening means for interconnecting the separate garments, such fastening means being adapted for engagement with complementary fastening means on an adjacent article, the respective fastening means being associated with respective strips or tapes bridging a plurality of conductive fibres incorporated in each of the articles to provide electrical continuity. The articles may comprise an upper body or jacket portion of a garment and a lower body or trouser portion. Alternatively, or in addition, the articles may comprise a hood together with an upper body portion or a unitary upper and lower body portion of a garment. In either case the lower body portion of the garment may incorporate integral or separate articles of footwear.

Alternatively, the articles may comprise a complete body garment or a lower body garment and associated articles of footwear, said electrically conductive member extending across the junction of one article to the other and being connected to or juxtaposed with one or both of the articles.

Alternatively, an electrically conductive member may be associated with each article, the electrically conductive members incorporating complementary fastening members adapted for engagement with one another to secure the articles together and form an electrically conducting path between them. The complementary fastening members may comprise components of a press or stud fastener.

In an alternative arrangement the workwear may comprise an electrically conductive stirrup, opposite ends of which are secured to lower edge regions of leg portions of a garment, the stirrup being adapted to extend beneath the wearer's foot in

M 0 1 . 0 4 . 0 0

- 5 -

contact with an article of footwear having an electrically conductive sole. The stirrup member may be located around the wearer's foot internally of the article of footwear whereby to be compressed in use between the wearer's foot and the inner surface of the conductive sole of the article of footwear.

- 5           Alternatively, the stirrup member may be arranged to extend around the outer surface of an article of footwear whereby to be compressed in use between the outer surface of the conductive sole of the article of footwear and the floor.

- Each strip or tape incorporates a plurality of electrically conductive yarns which may comprise filaments formed from or coated with electrically conductive material.
- 10          The strip or tape may advantageously be formed from woven polyester fabric incorporating electrically conductive yarns. In a typical construction the electrically conducting yarns in the strip or tape from which the articles are constructed are arranged to form a 5mm grid pattern, the electrically conducting fibres in the electrically conducting member being arranged in parallel lines approximately 2mm apart.

- 15          It is believed that the use of a strip or tape with conductive elements woven into it in such a way as to protrude from the surface of the strip or tape helps to enhance electrical conductivity in two ways:

1.       The protrusions are forced into the fabric of the seam by virtue of the stitching, ensuring physical contact between the electrically conductive elements in the
- 20       strip or tape and those in the fabric of the component; and

2.       The protrusions formed by the sharply bent conductive yarns may promote corona discharge at above about 500 volts, so increasing the rapid conduction of charge across the seams. It is thought that this corona discharge is responsible for the extremely rapid and successful discharge from the made up antistatic workwear.

- 25          In addition, antistatic workwear in accordance with the invention has been found to retain its ability to dissipate electrostatic charge after repeated cleaning and sterilisation treatment. For example, workwear subjected to 60 typical wash and wear cycles has shown no significant change in the ability to dissipate charge, and equally workwear subjected to 60 gamma radiation sterilisation cycles also displayed no loss of electrical
- 30       bonding in the seams. Workwear in accordance with the invention is therefore consid-

H 01.04.00

- 6 -

erably more economical in use, lasting many more cycles of use and cleaning/sterilisation than conventional antistatic workwear.

### Brief Description of the Drawings

Embodiments of the invention will now be described, by way of example only, with reference to the drawings, which are diagrammatic and in which:-

Figure 1 is an illustration of an article of workwear incorporating one embodiment of the invention;

Figure 2 is a perspective view showing the manner of interconnection of adjacent panels of the garment shown in Figure 1;

Figure 3 is an enlarged cross-section through the seam formed between the adjacent panels shown in Figures 1 and 2;

Figure 4 is an illustration of fabric and tape constructions incorporated in the embodiment of Figures 1 to 3;

Figures 5 and 6 show alternative means of interconnecting the components of a garment similar to that shown in Figure 1;

Figure 7 shows a means of electrically interconnecting a sleeve and cuff of a similar garment;

Figure 8 illustrates a method of interconnecting a garment and articles of footwear according to a further embodiment of the invention;

Figure 9 is an enlarged fragmentary side view of part of the embodiment shown in Figure 8;

Figure 10 shows a further method of interconnecting a garment with a hood and with articles of footwear;

Figure 11 is an enlarged cross-section showing the manner of interconnection in the arrangement of Figure 10;

Figure 12 is a side view of the arrangement shown in Figure 10; and

Figure 13 is an enlarged cross-sectional view of a section of the tape in contact with a piece of the conductive fabric.

### Detailed Description of the Illustrated Embodiments

Referring to Figures 1-3, antistatic workwear comprises an overall having four components, namely a main body component 10, first and second arm components 11

M 01.04.00

- 7 -

and a trouser or lower body component 12 comprising two leg portions 13. Each of the components is constructed from a woven cleanroom fabric such as continuous filament polyester and incorporates a grid of electrically conductive yarns 21 generally constructed from polyester and carbon and typically spaced apart by intervals of 5mm or more. This electrically conductive grid defined by the conductive yarns 21 forms a path for localised electrical static charge to be dissipated across the conductive grid.

The main body component 10 is connected to the arm components 11 by seams 15 and to the lower body component 12 by a seam 16. In order to ensure electrical continuity between the components, across the seams 15 and 16, each of the seams incorporates an electrically conductive member defined by a strip or tape 20 of electrically conductive material as best seen in Figures 2 and 3. For this purpose the edge regions of each component are folded into generally hook or U-shaped configuration and engaged with one another as shown in Figure 2 and 3 so that two layers 17A, 17B of one component and two layers 18A, 18B of the adjacent component overlies one another. A strip or tape 20 of electrically conductive material is located between adjacent portions 17A and 18B of the overlapping components and the assembly is secured together by lines of stitching indicated diagrammatically at 19A and 19B. The strip or tape 20 of electrically conducting material is thus clamped between the overlapping portions of the two components and extends longitudinally for the full length of the associated seam 15 or 16.

The strip or tape 20 is formed from polyester fabric incorporating a plurality of electrically conductive yarns 22 formed, for example, from carbon coated nylon or conductive polyester yarns. The conductive yarns 22 are woven through the strip or tape 20 and come frequently to the surface where they are bent around the yarns forming the main portion of the strip or tape 20 and thus project from the surface of the tape, typically by 0.5-1.0mm. In this way the projecting conductive yarns 22 in the strip or tape 20 are pressed into contact with the conductive yarns in the component 21, thereby enhancing the electrical contact between them. In addition, the relatively sharp bends in the conductive yarns 22 promote corona discharge within the fabric of the component at voltages above about 500V, ensuring transfer of charge even where

01-04-00

- 8 -

there is no direct contact between the conductive yarns 21 of the fabric of the component and the conductive yarns 22 in the strip or tape 20.

Figure 4 shows a component 10 made from a typical garment fabric 10 and strip or tape 20 to scale, the electrically conductive yarns 21 in the component forming a grid of 5mm mesh size compared with a 2mm spacing of the electrically conductive yarns 22 of the strip or tape 20. The conductive yarns 22 are exposed at the surface of the tape at the zones 22A indicated by heavy lines in Figure 4. The conductive yarns 22 are also of larger diameter than the conductive yarns 21, generally being of the order of 0.5-1.0mm in diameter compared with 0.01-0.05mm diameter for the conductive yarns 21. By virtue of the close spacing of the conductive yarns 22 compared with the grid size of the conductive yarns 21 and the relatively high degree of exposure of the conductive yarns 22 at the surface of the tape 20, the conductive yarns 22 make contact with a high proportion of the conductive yarns 21 in the overlapping portions 17A, 18B of the adjacent components of the antistatic workwear and provide an effective electrical connection between them. This enables the antistatic workwear to be earthed from a single point since the electrical continuity which exists in the individual components by virtue of the conductive yarns 21 woven into the fabric, is continued across the seams 15 and 16 by virtue of the electrically conductive strip or tape 20 incorporated in the seams.

Figure 5 shows an alternative arrangement in which electrical continuity between components 10, 11 and 12 of antistatic workwear is maintained across interconnecting seams 15 and 16 by short lengths of electrically conductive strip or tape 20 similar to the strip or tape 20 described with reference to Figures 1 to 4. In this embodiment short sections of the strip or tape 20 are arranged to bridge the seams 15 and 16, each section being connected at its opposite ends by sewing or other suitable means to the respective components 10, 11 or 10, 12. In this way the loss of electrical continuity across the seams is compensated by the electrical "bridges" formed by a plurality of strips or tapes 20. The number of strips or tapes 20 employed may be varied dependent on the spacing of the electrically conductive yarns 21 forming the grid in the fabric of the component, the length of the seams and the measured electrical conductivity across the seams.

11 01.04.00

- 9 -

Figure 6 shows an alternative means of improving electrical conductivity across seams of a unitary article of antistatic workwear in which electrically conductive strip or tape 20, of similar construction to that described with reference to Figures 1 to 4, is sewn to the surface of the antistatic workwear and extends across the components from which the garment is constructed. In the embodiment shown in Figure 6 a first length of strip or tape 20A extends from one arm component 11 across the main body component 10 to the other arm component 11, thereby bridging the seams 15 formed between the main body component 10 and the two arm components 11. A second length of electrically conductive strip or tape 20B extends across the main body component 10 and down one leg portion 13 of the lower body component 12. A strip or tape 20B intersects and is secured to the strip or tape 20A adjacent the upper region of the main body component 10 and thereby provides electrical continuity between the arm components 11, the main body component 10 and the leg portion 13 of the workwear. Figure 6 also shows an extension 20C of the strip or tape 20B connected to an integral hood portion 23 of the workwear connected to the main body component 10 by a seam 24. In this way electrical continuity is maintained between all the components making up the workwear thereby enabling it to be earthed from a single point.

Figure 7 shows an embodiment of the invention employed to establish electrical connection between an arm component 11 constructed from fabric incorporating conductive yarns 21 as previously described, and a cuff component 11A. Generally such cuff components are formed from electrically conductive knitted yarns and serve to ensure close contact between the workwear and the wearer's skin. In the arrangement shown in Figure 7 electrically conductive strip or tape 20, similar to that described above, is sewn onto the arm component 11 and projects beyond the end of the arm component 11 over the cuff component 11A. The strip or tape 20 is connected to a metallic stud-type fastener 25 which is secured to the cuff component 11A and is adapted to form a terminal by means of which the antistatic workwear can be connected to earth. The strip or tape 20 bridges the seam 26 between the arm component 11 and the cuff component 11A thereby maintaining electrical conductivity from the arm component to the cuff component in the manner previously described. The electrical connection between the stud-type fastener 25, the strip or tape 20 and the cuff

11 01 04 00

- 10 -

component 11A may be enhanced, if desired, by attachment of a section of the fabric 27 from which the arm component and the remainder of the workwear is constructed around the area of the stud-type fastener 25. The strip or tape 20 may be relatively short in length as illustrated in Figure 7 serving simply to bridge the seam 26. Alternatively the strip or tape 20 may comprise a terminal portion of a strip or tape which extends to other parts of the workwear in the manner illustrated, for example, in Figure 6.

Figures 8 and 9 show an alternative arrangement in which electrical continuity is maintained between a one piece item or antistatic workwear 30 and a separate article of footwear (not shown). As shown in the drawing the item of workwear 30 is of integral one piece construction comprising a hood component 31 and a body component 32 incorporating integral arm components 33 and integral leg portions 34. The item or workwear is constructed from a cleanroom fabric incorporating electrically conductive yarns in the manner previously described and electrical continuity is therefore maintained throughout the item of workwear by virtue of the conductive fibres incorporated in its construction. A stirrup 35 is fitted to the lower end of each leg portion 34 and is formed from similar electrically conductive cleanroom fabric incorporating a grid of conductive yarns. The stirrup is connected at each of its ends to the lower edge of the associated leg portion 34 and is adapted in use to extend under the user's foot 36 and inside a separate article of footwear (not shown).

In order to enhance electrical conductivity between the item of workwear and the stirrup 35, a strip or tape 37 of electrically conductive material, similar to that described with reference to the previous embodiments, is sewn into the stirrup 35 and projects at opposite ends where it is sewn to the lower region of the leg portion 34. In this way the electrically conductive strip or tape bridges the seams between the stirrup and the associated leg portion 34 and maintains electrical continuity between the conductive grids incorporated in the fabrics from which both components 34 and 35 are formed. A stud 38 may be provided on the stirrup 35 for connection of an ankle earth if required.

The articles of footwear worn by operatives are conventionally provided with electrically conductive soles whereby the operative is earthed to the floor. By virtue of

01-04-00

- 11 -

the arrangement described with reference to Figures 8 and 9, the operative's workwear is earthed through the conductive sole by virtue of the electrically conductive strip or tape 37 which connects with the main body component of the workwear and the stirrup 35 and thereby enables the entire item or workwear to be earthed from the stirrups 35 fitted to each of the leg portions 34.

While in the arrangement shown in Figures 8 and 9 the workwear is illustrated as being of integral construction, in practice it will usually comprise separate components interconnected by seams in the manner described with reference to Figures 1 to 6. In that event the components from which the workwear is constructed are preferably interconnected by electrically conductive strip or tape in the manner described with reference to these figures, thereby ensuring electrical continuity is maintained across the seams. Alternatively the workwear may comprise separate hood, body and leg components in which event these are preferably interconnected using electrically conductive strip or tape and suitable fasteners 48A and 48B in the manner to be described with reference to Figures 10 to 12 of the drawings, to maintain electrical continuity between the separate components making up the overall item of workwear.

Figures 10 to 12 show a means of maintaining electrical continuity between separate components which together form a complete item of workwear comprising an integral body component 40 incorporating arm components and leg portions 41 and 42, a separate hood component 43 and separate shoes or boots 44 adapted to be fitted over the lower portions of the leg portions 42. The hood component 43 is adapted to overlies the upper region of the body component 40. At the area where the two components overlap, short sections of electrically conductive strip or tape 20, similar to that described with reference to Figures 1 to 4, are sewn into the lower edge region of the hood component 43 and the neck region of the body component 40 respectively. Each section of conductive strip or tape is fitted with a respective part of a stud or other suitable fastener 45 which engages the conductive strip or tape which in turn is in contact with the grid of electrically conductive yarns woven into the fabric from which the components are made. Each part of the stud fastener is therefore electrically connected to the associated component and when the workwear is fitted and the stud fasteners interconnected, electrical continuity is effected between the separate components.

M 0 1 . 0 4 . 0 0

- 12 -

The boots 44 are connected to the leg portions 42 of the workwear in a similar fashion. As shown in Figures 11 and 12, a strip or tape 46 of electrically conductive material similar to that described with reference to Figures 1 to 4, is sewn into an upper region of each boot 44 and a similar strip or tape 47 is sewn on to the adjacent lower region of each leg portion 42. Each section of strip or tape bridges a number of the  
5      yarns forming the conductive grid in the fabric from which the boot and body component are formed and respective parts 48A, 48B of a stud fastener are fitted to the strip or tape connected to each component. When the boot is fitted over the lower end of the leg, the respective parts of the stud fastener are engaged thereby forming electrical  
10     continuity between the shoe or boot and the workwear as a whole.

Although not shown in Figure 10, the arm and body components and the leg portions of the workwear are preferably electrically interconnected across the seams between them by any of the means shown in Figures 1, 5 or 6 of the drawings.

By virtue of the arrangements described, electrical continuity may be maintained  
15     across seams of a single item of workwear or between separate components forming a complete item of workwear. This enables the workwear to be earthed from a single point, such as from a cuff or ankle, or through an article of footwear in the manner described with reference to Figures 7 to 12 of the drawings. The arrangements described are also of simple construction yet provide an effective means of maintaining electrical  
20     continuity throughout workwear consisting of multiple interconnected components and/or multiple separate components, thereby enabling static electrical charges to be dissipated without requiring complex multiple earthing arrangements. The construction of the strip or tape is also such that it will withstand repeated exposure to commercial  
laundrying cycles without loss of electrical conductivity.

25     Figure 13 shows, in exaggerated form, the relationship between the conductive yarns in the strip or tape and those in the fabric in a seam. The strip or tape 130 has conductive yarns 131 woven into it in a relatively tight stitch or weave so that the yarns 131 protrude from each face in sharp bends 131A. The fabric of the component is represented by smaller non-conductive yarns 132 and larger conductive yarns 133  
30     spaced therein. It will be appreciated, however, that the relative sizes of the yarns 132 and 133 are not intended to be accurate representations of the relative sizes in reality.

M 01.04.00

- 13 -

The conductive yarns 131 of the strip or tape 130, while being pressed into contact with some of the yarns 133, exhibit sharp bends 131A which pass close to others of the conductive yarns 133, and the corona discharge effect at the sharp bends ensures that charge is transferred effectively between the conductive yarns 133 of a component of the workwear and the conductive yarns 131 of the strip or tape 130, and from there to the conductive yarns in another component of the workwear, ensuring that any static charge is quickly dissipated through the workwear to the earthing point, for example the floor, through conductive shoe soles, for example.

Various modifications may be made without departing from the invention. For example the invention may be applied to a wide range of workwear consisting of multiple separate components or incorporating seams in a variety of different locations. The fabric from which the workwear is constructed may vary as regards its material and the nature and extent of the electrically conductive yarns incorporated in it. For example while such conductive yarns are normally incorporated in a grid formation, they may alternatively be incorporated in the form of stripes. The electrically conducting strip or tape employed in the embodiments may be constructed in a wide variety of alternative forms provided it has a substantial electrically conductive surface area adapted to bridge a plurality of the conductive yarns incorporated in the fabric from which the components of the workwear are constructed to thereby maintain electrical continuity throughout the item of workwear. The strip or tape may also be secured to the inside or outside surfaces of the components by sewing or other suitable means.

Moreover, while reference has been made herein primarily to effecting electrical continuity between components of items of workwear, the invention may also be applied to other situations where it is necessary to maintain electrical continuity across seams, joins or other areas where a break in electrical continuity would otherwise occur.

M 01.04.00  
- 14 -**CLAIMS**

1. Antistatic workwear comprising a plurality of components (10, 11, 12, 31, 32, 33, 34 or 35) incorporating electrically conductive yarns (21), and an electrically conductive member (20, 20A, 20B, 20C, 37, 46 or 130) bridging the junction between adjacent components (10, 11, 12, 31, 32, 33, 34 or 35), characterised in that the electrical conductivity between adjacent components is enhanced by forming the electrically conductive member (20, 20A, 20B, 20C, 37, 46 or 130) from a strip or tape incorporating a plurality of electrically conductive yarns (22 or 131) which are of larger diameter than the conductive yarns (21), have alternate portions exposed at opposite sides of the strip or tape, and are pressed into conducting engagement with at least some of the conductive yarns (21) in both adjacent components.
2. Antistatic workwear, according to Claim 1, in which the conductive yarns (22 or 131) are sharply bent by the structure of the strip or tape to promote a corona discharge.
3. Antistatic workwear, according to Claim 1 or 2, in which the conductive yarns (21) are more widely spaced than the conductive yarns (22).
4. Antistatic workwear, according to any preceding claim, in which the conductive yarns (21) have a diameter of between 0.01 - 0.05mm.
5. Antistatic workwear, according to any preceding claim, in which the conductive yarns (22) have a diameter of between 0.5 - 1.0mm.
6. Antistatic workwear, according to any preceding claim, in which the strip or tape is stitched (19A, 19B) to each of the adjacent components (10, 11, 12, 31, 32, 33, 34 or 35).
7. Antistatic workwear, according to any preceding claim, in which at least some of the yarns (21 or 22) are formed from a carbon-coated polyamide or a conductive polyester.
8. Antistatic workwear, according to any preceding claim, in which the strip or tape is incorporated longitudinally into a seam (15 or 16) formed between adjacent components (10, 11, 12, 31, 32, 33, 34 or 35).

M 01.04.00

- 15 -

9. Antistatic workwear, according to any preceding claim, in which the strip or tape extends transversely of a seam (15 or 16) formed between adjacent components (10, 11, 12, 31, 32, 33, 34 or 35).

10. Antistatic workwear, according to Claim 9, in which a plurality of strips or tapes extend transversely across the same seam (15 or 16).

11. Antistatic workwear, according to any preceding claim, in which at least one strip or tape (20) is connected to a terminal (25) for connecting the workwear to earth.

12. Antistatic workwear, according to any preceding claim, which includes a component (42) defining a leg portion of the workwear and a shoe or boot (44) defining another portion of the workwear, and the boot (44) is connected to the component (42) by a fastener (48A, 48B) to provide electrical continuity.

13. Antistatic workwear, according to any preceding claim, in which the components comprise a plurality of separable components (31, 32, 33, 34, 35, 44) and the strips or tapes incorporate fastening means (25, 38, 48A, 48B) for interconnecting the separable components (31, 32, 33, 34, 35, 44) to provide electrical continuity.

14. Antistatic workwear, according to any preceding claim, in which one or more of the strips or tapes provide an electrically conducting path extending from a cuff (11A) to boots (44).

15. Antistatic workwear, according to any preceding claim, having a leg portion (34) arranged in conducting engagement with an electrically conductive stirrup (35) arranged to extend beneath the wearer's foot in electrical contact with an article of footwear having a conductive sole.

PCT  
ENT COOPERATION TREATY

PCT

## NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:

Assistant Commissioner for Patents  
United States Patent and Trademark  
Office  
Box PCT  
Washington, D.C.20231  
ÉTATS-UNIS D'AMÉRIQUE

in its capacity as elected Office

Date of mailing (day/month/year) 01 November 1999 (01.11.99)	
International application No. PCT/GB99/00595	Applicant's or agent's file reference P62831
International filing date (day/month/year) 26 February 1999 (26.02.99)	Priority date (day/month/year) 26 February 1998 (26.02.98)
Applicant HURST, Norman, John, Alfred et al	

1. The designated Office is hereby notified of its election made:

☒ in the demand filed with the International Preliminary Examining Authority on:  
27 September 1999 (27.09.99)

☐ in a notice effecting later election filed with the International Bureau on:  
\_\_\_\_\_

2. The election ☒ was  
☐ was not

made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland	Authorized officer S. Mafla
Facsimile No.: (41-22) 740.14.35	Telephone No.: (41-22) 338.83.38